

Gobius 4

Gobius®



Gobius 4 for all tanks

Measuring from the outside of the tank using the 'knock & listen' method

The Gobius 4 is extremely easy to install. It takes no more than 30 minutes and avoids the need to take the tank apart or drill unnecessary holes, making it an ideal product for retro fitting to tanks already in service.

Suitable for tanks containing waste, water or Diesel

Tank Wall Thickness

Mild steel (1-3mm),

Stainless steel (1-3mm),

Aluminum (2-5mm)

Plastic (2-10mm) or GRP (4-8mm) no matter what size or shape of tank.

Installed and ready to use in 30 minutes!

The perfect tank monitor for your waste tank whether it is in metal or plastic.

LEDs of different colors show four levels; Empty, 1 / 4-, 1 / 2- and 3/4-full.

3 sensors mounted (glued) with a 3M adhesive tape on the outside of your tank.

Technical Specifications

Supply Voltage	11 ~ 29 V DC
Supply Current:	200 mA max. (Operating), 50 mA max. (Idle)
Water Connection	½" BSP
Lamp driver outputs:	29 V DC max, 200 mA max
Analogue Instrument outputs:	4-20 mA current loop, 10-190 Ω, 240-33 Ω, 0-5 Volt DC
Max. voltage:	29 VDC

Part No:	12/24VDC
Waste	970442
Fuel & Water	970497

System Illustration

